

Recommended Rope Requirements Per Boat (updated 22/11/24)

Rope Description	Rope Type	Colour	Diameter	Quantity	Length (m)
Main Sheet	Polyester Double Braid	Blue	6mm	1	8
Jib Sheet	Polyester Double Braid	Red	6mm	1	7
Screecher Sheet	Polyester Double Braid	Green	8mm	1	11.5
Tapered Main Halyard (0.8m Tapered To Core For Halyard Lock)	Dyneema Core Polyester	Blue	5mm	1	12
Jib Halyard	Dyneema Core Polyester	Red	4mm	1	8.5
Screecher Halyard	Dyneema Core Polyester	Green	4mm	1	10
Screecher Furler Line	Marlow Excel Control Line	Green	5mm	1	9.5
Screecher Block Ties	Dyneema Core Polyester	Black	3mm	2	0.8
Forestay Tie	Dyneema Core Polyester	Black	3mm	1	1.2
Cunningham	Dyneema Core Polyester	Blue	4mm	1	2.5
Main Block Line to Deck	Dyneema Core Polyester	Black	3mm	1	0.8
Centerboard Handle	Polyester Double Braid	Any	6mm	1	0.6
Trampolines Inboard Tie	Dyneema Core Polyester	Blue	4mm	2	2.5
Trampolines Outboard Tie Across	Dyneema Core Polyester	Any	4mm	2	3
Trampolines Outboard Tie Along	Dyneema Core Polyester	Any	4mm	2	2.5
Trailer Sides	Polyester Double Braid	Any	6mm	2	2.2
Trailer Front Tie	Dyneema Core Polyester	Any	4mm	1	1
Forestay Ring Tie	Dyneema		8mm	1	0.8

Stay Lengths

Forestay	1 x 19 G316	Wire	2.5mm	1	4.7
Sidestay	1 x 19 G316	Wire	2.5mm	2	4.9

Self Tacker

Bow Tie For Block	Dyneema		2mm	1	0.7
Deck Sheet Block To Shackle	Dyneema		3mm	1	2.1
Car Control	Polyester Case Dyneema Core	red	3mm	1	2.1

Battens Supplied With Sails (All 10mm wide)

	Thickness (mm)	Length (cm)
9.3 Square Top		
B1 Bottom	5	191
B2	5	179
B3	5	160
B4	4	131
B5	4	100
B6 Top	4	82

8.3

B1 Bottom	5	186
B2	5	171
B3	4	142
B4	4	107
B5 Top	4	66